


Schweißfittings DIN 11852


Art.Nr. EUR Art.Nr. EUR

Schlauchtülle Zoll-Rohr



DN	A	B				AISI304	AISI316L-1.4404
1"	25,4	60				530703	8,50 530803
1,5"	38,1	80				530704	9,80 530804
2"	50,8	90				530705	11,40 530805
2,5"	63,5	100				530706	21,50 530806
3"	76,1	110				530707	26,20 530807
4"	101,6	120				530708	43,90 530808

Reduzierstück konzentrisch DIN 11852



DN	A	B	C	D		AISI304	AISI316L-1.4404
15-10	16	10	11	1,5		530959	9,10 531059
20-10	20	10	18	1,5		530960	10,70 531060
20-15	20	16	7	1,5		530961	9,50 531061
25-10 *	26	10	29	1,5		530962	29,40 531062
25-15	26	16	18	1,5		530963	12,80 531063
25-20	26	20	11	1,5		530964	11,90 531064
32-15 *	32	16	22	1,5		530965	12,60 531065
32-20	32	20	22	1,5		530966	10,90 531066
32-25	32	26	11	1,5		530967	8,60 531067
40-15 *	38	15	45	1,5		530968	42,10 531068
40-20	38	20	33	1,5		530969	11,80 531069
40-25	38	26	22	1,5		530970	12,10 531070
40-32	38	32	11	1,5		530971	11,40 531071
50-25	50	26	44	1,5		530972	15,20 531072
50-32	50	32	33	1,5		530973	14,10 531073
50-40	50	38	22	1,5		530974	12,70 531074
65-25	66	26	73	2		530975	50,10 531075
65-32 *	66	32	52	2		530976	47,90 531076
65-40	66	38	51	2		530977	15,70 531077
65-50	66	50	29	2		530978	16,20 531078
80-25 *	81	25	89,5	2		530979	76,20 531079
80-32 *	81	31	83	2		530980	75,30 531080
80-40 *	81	37	78	2		530981	59,40 531081
80-50	81	50	56	2		530982	26,80 531082
80-65	81	66	27	2		530983	21,30 531083
100-25 *	100	25	112	2		530950	Anfrage 531050
100-32 *	100	31	105,5	2		530940	90,60 531040
100-50 *	100	50	90	2		530984	72,40 531084
100-65	100	66	61	2		530985	34,70 531085
100-80	100	81	34	2		530986	27,40 531086
125-50 *	125	49	122,5	2		561754	Anfrage 561854
125-65 *	125	66	89,5	2		530987	108,20 531087
125-80	125	81	79	2		530988	60,20 531088

* Ähnlich DIN 11852

Die Toleranz der Wanddicke beträgt gemäß DIN-Norm je nach Nennweite -0,7 bis +0,7 mm.

LINNEMANN
Rohrverbindungen • Edelmetallarmaturen
Pipe connections • Stainless steel fittings

LINNEMANN GmbH • Heerweg 14-16
72070 Tübingen / Germany


Fon: +49 (0) 7071 97555-0
Fax: +49 (0) 7071 97555-10

E-Mail: info@linnemann-online.com
Internet: www.linnemann-online.com

Schweißfittings DIN 11852

Art.Nr. EUR Art.Nr. EUR

Reduzierstück konzentrisch DIN 11852




DN	A	B	C	D		AISI304		AISI316L-1.4404	
125-100	125	100	45	2		530989	43,30	531089	108,80
150-65 *	150	66	129	2		530958	130,10	531058	171,40
150-80 *	150	81	93	2		530990	135,10	531090	152,20
150-100	150	100	90	2		530991	73,20	531091	131,60
150-125	150	125	45	2		530992	44,90	531092	101,50
200-100 *	200	100	134	2		530993	217,20	531093	272,30
200-125 *	200	125	107,5	2		530994	199,90	531094	258,10
200-150	200	150	90	2		530995	165,20	531095	209,90

* Ähnlich DIN 11852

Die Toleranz der Wanddicke beträgt gemäß DIN-Norm je nach Nennweite -0,7 bis +0,7 mm.

Reduzierstück exzentrisch DIN 11852



DN	A	B	C	D		AISI304		AISI316L-1.4404	
15-10	16	10	16,5	1,5		531159	16,70	531259	20,20
20-10 *	20	10	27,5	1,5				531260	Anfrage
20-15	20	16	11	1,5		531161	18,40	531261	21,70
25-10 *	26	10	44	1,5		531162	Anfrage	531262	Anfrage
25-15	26	16	27,5	1,5		531163	22,40	531263	26,30
25-20	26	20	16,5	1,5		531164	22,40	531264	24,90
32-25	32	26	16,5	1,5		531167	22,30	531267	25,10
32-20	32	20	33	1,5		531166	26,20	531266	30,10
40-20 *	38	20	49,5	1,5				531269	Anfrage
40-25	38	26	33	1,5		531170	25,50	531270	26,30
40-32	38	32	16,5	1,5		531171	25,50	531271	27,60
50-25 *	50	26	46,5	1,5		531172	Anfrage	531272	Anfrage
50-32 *	50	32	33	1,5				531273	Anfrage
50-40	50	38	33	1,5		531174	25,10	531274	31,30
65-40 *	66	38	54	2		531177	Anfrage	531277	Anfrage
65-50	66	50	44	2		531178	31,10	531278	37,90
80-50 *	81	50	63	2		531182	Anfrage	531282	Anfrage
80-65	81	66	41	2		531183	38,90	531283	45,40
100-50 *	100	50	137,5	2		531184	Anfrage	531284	Anfrage
100-65 *	100	66	68	2		531185	Anfrage	531285	Anfrage
100-80	100	81	52,5	2		531186	51,80	531286	58,60
125-80 *	125	81	85,5	2		531188	Anfrage	531288	Anfrage
125-100	125	100	68,5	2		531189	72,40	531289	80,90
150-100 *	150	100	95,5	2		531191	Anfrage	531291	Anfrage
150-125	150	125	68,5	2		531192	72,40	531292	82,80

* Ähnlich DIN 11852

Die Toleranz der Wanddicke beträgt gemäß DIN-Norm je nach Nennweite -0,7 bis +0,7 mm.