





PTFE hoses for Food- and Sterile technique							Art.No	EUR	Art.No	EUR
 <b>PTFE corrugated hose, braided, spiral</b>	DN*	A	B	C	Pressure bar, 20 °C	Vacuum bar, 20 °C			Suction + pressure hose PTFE	
	15	19	9,5 **	1	41	0,8			6124-9,5x1	<a href="#">Enquiry</a>
	20	25	14,3 **	1,25	35	0,8			6124-14,3x1,25	<a href="#">Enquiry</a>
	25	32	20,6 **	1,65	31	0,8			6124-20,6x1,65	<a href="#">Enquiry</a>
	32	38	25,4 **	1,65	27	0,8			6124-25,4x1,65	<a href="#">Enquiry</a>
<p>– Minimum order quantity 1m – Only available with hose nozzles ready-for-use. Also anti-static available with conductive black PTFE. The hoses are also available with PTFE ined hose nozzles that will be beaded on the sealing surface. * nominal size / ** real size, inner-Ø between waves</p>										
 <b>PTFE corrugated hose, waveless, braided, flexible</b>	DN	A	B	C	Pressure bar, 20 °C	Vacuum bar, 20 °C			Suction + pressure hose PTFE	
	10	12,8	9,5	-	80	0,8			6128-9,5	<a href="#">Enquiry</a>
	13	17,8	13,5	-	70	0,8			6128-13,5	<a href="#">Enquiry</a>
	15	21,6	16,5	-	65	0,8			6128-16,5	<a href="#">Enquiry</a>
	20	24,4	19,8	-	60	0,8			6128-19,8	<a href="#">Enquiry</a>
	25	31,9	26,1	-	50	0,8			6128-26,1	<a href="#">Enquiry</a>
	32	39,5	32,5	-	45	0,8			6128-32,5	<a href="#">Enquiry</a>
	38	46,7	38,8	-	40	0,8			6128-38,8	<a href="#">Enquiry</a>
<p>– Minimum order quantity 1m – Only available with hose nozzles ready-for-use. Also anti-static available with conductive black PTFE. The hoses are also available with PTFE ined hose nozzles that will be beaded on the sealing surface.</p>										
 <b>PTFE corrugated hose, waveless, braided</b>	DN	A	B	C	Pressure bar, 20 °C	Vacuum bar, 20 °C			Suction + pressure hose PTFE	
	13	15,8	11,5	-	50	-			6132-11,5	<a href="#">Enquiry</a>
	16	20,8	15,5	-	50	-			6132-15,5	<a href="#">Enquiry</a>
	19	23,6	18,5	-	60	-			6132-18,5	<a href="#">Enquiry</a>
	25	27,7	22,8	-	40	-			6132-22,8	<a href="#">Enquiry</a>
	32	36,8	30,5	-	45	-			6132-30,5	<a href="#">Enquiry</a>
	38	43,1	36,6	-	40	-			6132-36,6	<a href="#">Enquiry</a>
	50	55,2	48,5	-	25	-			6132-48,5	<a href="#">Enquiry</a>
<p>– Minimum order quantity 1m – Only available with hose nozzles ready-for-use.</p>										
 <b>PTFE corrugated hose, waveless, braided, silicone cover</b>	DN	A	B	C	Pressure bar, 20 °C	Vacuum bar, 20 °C			Suction + pressure hose PTFE	
	6	11,6	6,4	-	130	0,8			6126-6,4	<a href="#">Enquiry</a>
	10	15,5	9,5	-	100	0,8			6126-9,5	<a href="#">Enquiry</a>
	13	19,5	12,7	-	70	0,8			6126-12,7	<a href="#">Enquiry</a>
	20	27,3	19	-	60	0,8			6126-19	<a href="#">Enquiry</a>
	25	34,8	25,4	-	50	0,8			6126-25,4	<a href="#">Enquiry</a>
<p>– Minimum order quantity 1m – Only available with hose nozzles ready-for-use. Also anti-static available with conductive black PTFE.</p>										